

AMENDMENTS TO THE SPECIFICATION

**Please amend paragraphs Nos. [241]-[244] as indicated below.**

A complete listing of all amended paragraphs is presented below with insertions underlined (e.g., insertion), and deletions struckthrough or in double brackets (e.g., ~~deletion~~ or ~~[[deletion]]~~).

[0241] Thus, in accordance with an aspect of at least one of the inventions disclosed herein, a suction tubing 5' illustrated in Figures 20 and 21 includes an inner diameter 130' ~~134'~~ of at least about 8 millimeters. More preferably, the inner diameter 130' ~~134'~~ of the tubing 5' is from about 8 millimeters to about 15 millimeters.

[0242] As such, the tubing 5' can include the same type of deformations occurring in the known suction tubing 128, yet retain a sufficient clearance within its inner dimension that the likelihood of clogging is not increased as greatly as that resulting from the deformed portions of the tubing 128 illustrated in Figure 19. For example, where the suction tubing 5' is formed with an inner diameter 130' ~~134'~~ of about 8 millimeters in a relaxed state, the suction tubing 5' can be deformed to some extent resulting in a minimum inner dimension identified by the reference numeral 158. Because the inner diameter 130' ~~134'~~ of the suction tubing 5' in a relaxed state is at least 8 millimeters, the reduced inner dimension 158 caused by a deformation can still be as large as 6 millimeters. Thus, where the tubing 5' has been damaged or deformed in the same manner as the known tubing 128, the tubing 5' is less likely to cause clogging in the same manner as the known tubing 128.

[0243] Optionally, the tubing 5' can include the same female connectors 126 described above with reference to Figure 15. However, such female adapters, for example, such as the female adapter 126' illustrated in Figure 21, can also include slight modifications to the inner recess 134, identified in Figure 21 as inner annular recess 134' ~~diameter-134'~~, so as to more readily accept the outer diameter 132' of the tubing 5'.

[0244] In another modification, a female adapter 126' included with the tubing 5' can define a larger inner diameter 130' ~~134'~~ than the inner surface 138 of the adapter 126. In use, it may be preferable to cut the adapter 124 so as to avoid the formation of a bottle neck in the vacuum circuit leading to the container 116.